

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

## XO2022A #WinterRacingDiesel

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name:** XO2022A #WinterRacingDiesel  
**Trade name(s):** Exocet #WinterRacingDiesel (XO2022A)  
**Product description:** Liquid fuel additive.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified use(s):** Liquid fuel additive.  
**Uses advised against:** Follow supplier's recommendations on correct use of the product.

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:** Fuel Additive Science Technologies Limited  
Unit 29, Atcham Business Park,  
Upton Magna, Shrewsbury,  
Shropshire, SY4 4UG  
**Telephone:** +44 (0)1743 761 415  
**E-mail:** info@fastexocet.co.uk

#### 1.4 Emergency telephone number

**In case of emergency, call:** 0333 333 9962 (24 hours, 7 days)

### SECTION 2: Hazard Identification

#### 2.1 Classification of the substance or mixture

##### 2.1.1. Classification according to Regulation (EC) No. 1272/2008 (CLP)

Acute Tox. 4; H302  
Asp. Tox. 1; H304  
Acute Tox. 4; H312  
Skin Irrit. 2; H315  
Acute Tox. 4; H332  
Carc. 2; H351

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

Aquatic Chronic 2; H411  
EUH044

## 2.1.2. Classification according to Directive Directive 1999/45/EC

Harmful; Xn; R20/21/22  
Carc. Cat. 3; Xn; R40  
R44  
Harmful; Xn; R65  
R66  
Dangerous for the environment; N; R51/53

## 2.2 Label elements

### 2.2.1. Label according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictogram(s):



Signal Word:

Danger.

Hazard Statement(s):

H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H332: Harmful if inhaled.  
H351: Suspected of causing cancer.  
H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s):

P261: Avoid breathing vapours  
P271: Use only outdoors or in a well-ventilated area.  
P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
P331: Do NOT induce vomiting.  
P405: Store locked up.  
P501: Dispose of contents/container to: disposal should be in accordance with local, state or national legislation.

Supplemental Hazard information (EU):

EUH044: Risk of explosion if heated under confinement.

## 2.3 Other hazards

The product does not contain substances assessed to be PBT or vPvB.

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

## SECTION 3: Composition

### 3.2 Mixtures

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification (Regulation (EC) No. 1272/2008 (CLP))	Classification (Directive 67/548/EEC)
2-Ethylhexyl nitrate <i>REACH: 01-2119539586-27-XXXX</i>	40-80	27247-96-7	248-363-6	-	Acute Tox. 4; H302 Acute Tox. 4; H312 Acute Tox. 4; H332 Aquatic Chronic 2; H411 EUH044 EUH066	Xn; R20/21/22 R44 N; R51/53 R66
Fuels, diesel, no. 2	3-10	68476-34-6	270-676-1	649-227-00-2	Asp. Tox. 1; H304 Skin Irrit. 2; H315 Acute Tox. 4; H332 Carc. 2; H351 STOT RE 2; H373 (Thymus, liver, bone marrow) Aquatic Chronic 2; H411	Xn; R20 Xi; R38 Carc. Cat. 3; R40 Xn; R65 N; R51/53
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	1-3	-	918-481-9	-	Asp. Tox.1 ; H304 EUH066	Xn; R65 R66
2-Ethylhexan-1-ol <i>REACH: 01-2119487289-20-XXXX</i>	0-2	104-76-7	203-234-3	-	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	Xn; R20 Xi; R36/37/38
Butanedioic acid, polyisobutenyl Polymer	0-2	-	-	-	Eye Irrit. 2; H319	Xi: R36
Solvent naphtha (petroleum), heavy arom.	0-1	64742-94-5	265-198-5	649-424-00-3	Asp. Tox. 1; H304 Skin Irrit. 2; H315 Aquatic Chronic 2; H411	Xi; R38 Xn; R65 N; R51/53

See Section 16 for full description of R phrases and H statements.

## SECTION 4: First Aid Measures

### 4.1 Description of first aid measures

**INHALATION:** Remove person to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, get medical advice/attention.

**SKIN CONTACT:** Remove contaminated clothing immediately. Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If irritation persists or if you feel unwell, get medical advice/attention.

**EYE CONTACT:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing making sure to rinse under eyelids. If eye irritation persists, get medical advice/attention.

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

**INGESTION:** Obtain immediate medical attention. Do not induce vomiting. If vomiting occurs, the head should be kept low to avoid vomit entering the lungs. Provided the patient is conscious, rinse mouth out with water and provide patient with 200-300 mL of water to drink. Never give anything by mouth to an unconscious person.

## 4.2 Most important symptoms and effects, both acute and delayed:

Skin contact causes irritation and redness. Repeated exposure may cause skin dryness or cracking. Eye contact may cause slight irritation, watering and redness. If swallowed, aspiration into lungs may result in chemical pneumonia. Ingestion may cause discomfort and nausea.

Suspected of causing cancer.

## 4.3 Indication of any immediate medical attention and special treatments needed:

In case of accident or if patient feels unwell, seek medical advice immediately. If swallowed, patient should be monitored for signs of breathing difficulty as effects of aspiration may be delayed for up to 48 hours. If breathing is laboured, oxygen should be administered by qualified personnel.

## SECTION 5: Fire-fighting Measures

### 5.1 Extinguishing Media

**Suitable extinguishing media:** Foam, CO<sub>2</sub> or dry powder.  
For large fires, use water spray.

**Unsuitable extinguishing media:** Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Combustible liquid and vapour: Vapour may form explosive mixture with air. Vapour is heavier than air and may accumulate in confined spaces. Risk of explosion if heated under confinement. Containers exposed to heat may burst due to increase in pressure.

Combustion may liberate toxic fumes: Carbon monoxide, carbon dioxide, nitrogen oxides, various hydrocarbons.

### 5.3 Advice for fire-fighters

A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Move undamaged containers from fire area if this can be done safely. Keep fire exposed containers cool by spraying with water. Do not allow product or run-off to enter drains, sewers or watercourses.

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

## SECTION 6: Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

Eliminate sources of ignition. Ensure adequate ventilation. Evacuate area and keep upwind. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. Wear suitable personal protective equipment. Wear appropriate respirator when ventilation is inadequate. (See Section 8).

#### 6.1.2 For emergency responders

Keep unnecessary personnel away. Wear suitable protective clothing (See Section 8). Contaminated clothing should be thoroughly cleaned.

### 6.2 Environmental precautions

Collect spillage. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

### 6.3 Methods and materials for containment and cleaning up

#### 6.3.1 For containment

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable adsorbent material.

#### 6.3.2 For cleaning up

Use sand, earth or any suitable non-combustible adsorbent material to adsorb spillages. Using non-sparking tools transfer the contaminated adsorbent material into a container for disposal. The containers used should be plastic-lined sealable drums. Containers should be sealed before being disposed of via an authorised waste disposal contractor.

#### 6.3.3 Other advice

None.

### 6.4 Reference to other sections

See Section 8 for personal protective equipment. See Section 13 for waste disposal.

## SECTION 7: Handling and Storage

### 7.1 Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Provide adequate ventilation, including

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

local extraction, to minimise exposure to vapours. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. Wear suitable personal protective equipment (See Section 8).

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off immediately all contaminated clothing and wash it before reuse. Contaminated clothing should be thoroughly cleaned or disposed of as hazardous waste.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Keep cool. Protect from direct sunlight. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store only in the original container. Empty containers retain product residue and can be hazardous.

Keep away from oxidising agents.

## 7.3 Specific end uses(s)

Liquid fuel additive.

## SECTION 8: Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Workplace exposure limits

Source: EH40/2005, 2<sup>nd</sup> Ed., 2011.

No workplace exposure limits assigned.

#### DNELs (Workers)

Substance	Route	Acute/short-term exposure		Long-term exposure	
		Systemic effects	Local effects	Systemic effects	Local effects
2-Ethylhexyl nitrate	Inhalation			0.24 mg/m <sup>3</sup>	
	Dermal			0.69 mg/kg bw/day	0.044 mg/cm <sup>2</sup>
2-Ethylhexan-1-ol	Inhalation	-	106.4 mg/m <sup>3</sup>	53.2 mg/m <sup>3</sup>	-
	Dermal	-	-	23 mg/kg bw/day	-

#### PNECs

Substance	Aqua (fresh water)	Aqua (marine water)	Aqua (intermittent releases)	Sewage Treatment Plants	Sediment (fresh water)	Sediment (marine water)	Soil	Oral
2-Ethylhexyl nitrate	0.0008 mg/L	0.00008 mg/L	-	10 mg/L	0.00074 mg/kg sediment dw	0.00074 mg/kg sediment dw	0.000191 mg/kg soil dw	-

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

Substance	Aqua (fresh water)	Aqua (marine water)	Aqua (intermittent releases)	Sewage Treatment Plants	Sediment (fresh water)	Sediment (marine water)	Soil	Oral
2-Ethylhexan-1-ol	0.017 mg/L	0.0017 mg/L	0.17 mg/L	10 mg/L	0.28 mg/kg sediment dw	0.028 mg/kg sediment dw	0.047 mg/kg soil dw	55 mg/kg food

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Provide adequate ventilation, including local extraction, to minimise exposure to vapours.

### 8.2.2 Personal protection

**Eye protection:** Goggles or safety glasses with side shields giving complete protection to eyes. (EN 166)

**Skin protection:**

**Hand protection:** Chemical resistant gloves (EN 374). Viton gloves are recommended. Contact glove supplier to confirm suitable glove material, thickness and breakthrough times.

**Other:** Long sleeve protective clothing. Plastic apron. Rubber boots.

**Respiratory protection:** In the case of insufficient ventilation, wear respiratory equipment suitable for organic gases and vapours with a boiling point above 65°C. (EN 14387)

**Thermal hazards:** Wear suitable temperature resistant gloves and protective clothing if the product is heated.

### 8.2.3 Environmental exposure controls

Inform environmental manager of all incidents involving this product.

## SECTION 9: Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

**Appearance:** Light brown liquid.

**Odour:** Aromatic.

**Odour threshold:** Not available.

**pH:** Not applicable.

**Melting/freezing point:** Not available.  
2-Ethylhexyl nitrate: < -50°C

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

<b>Initial boiling point and boiling range:</b>	Not available. 2-Ethylhexyl nitrate: > 100°C (decomposes)
<b>Flash point:</b>	Not available. 2-Ethylhexyl nitrate: 76.1°C [Pensky-Martens. ASTM D93 ISO 2719]
<b>Evaporation rate:</b>	Not available. 2-Ethylhexyl nitrate: < 1 (butyl acetate = 1)
<b>Flammability (solid; gas):</b>	Not applicable.
<b>Upper/lower flammability or explosive limits:</b>	Not available. 2-Ethylhexyl nitrate: Lower: 0.25%
<b>Vapour pressure:</b>	Not available. 2-Ethylhexyl nitrate: 0.03 kPa (0.2 mm Hg) (20°C)
<b>Vapour density:</b>	> 1 (Air = 1)
<b>Relative density:</b>	~ 1 (Water = 1)
<b>Solubility(ies):</b>	Very slightly soluble in water.
<b>Partition coefficient: n-octanol/water:</b>	Not available. 2-Ethylhexyl nitrate: Log Pow: 3.74 – 5.24
<b>Auto-ignition temperature:</b>	Not available. 2-Ethylhexyl nitrate: 130 - 215°C
<b>Decomposition temperature:</b>	Not available. 2-Ethylhexyl nitrate: > 100°C
<b>Viscosity:</b>	Not available. 2-Ethylhexyl nitrate: Dynamic: 1.7 mPa.s Kinematic: 1.3 cSt (40°C)
<b>Explosive properties:</b>	Not explosive. Risk of explosion if heated under confinement. Vapour may form explosive mixture in air.
<b>Oxidising properties:</b>	Not oxidising.
<b>9.2 Other information</b>	None.

## SECTION 10: Stability and Reactivity

<b>10.1 Reactivity</b>	Reacts with oxidising agents.
<b>10.2 Chemical stability</b>	Stable under normal conditions. Risk of explosion if heated under confinement.



# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

<b>10.3 Possibility of hazardous reactions</b>	No hazardous reactions expected during normal use.
<b>10.4 Conditions to avoid</b>	Keep away from sources of ignition, heat, hot surfaces, direct sunlight. Contact with incompatible materials.
<b>10.5 Incompatible materials</b>	Oxidising agents.
<b>10.6 Hazardous decomposition products</b>	Combustion may liberate toxic fumes: Carbon monoxide, carbon dioxide, nitrogen oxides and various hydrocarbons.

## SECTION 11: Toxicological Information

### 11.1 Information on toxicological effects

#### Acute toxicity

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

No data available on the mixture. The following data are for the product components:

2-Ethylhexyl nitrate:

LD<sub>50</sub> (oral/rat): > 9,640 mg/kg

LD<sub>50</sub> (dermal/rabbit): > 4,820 mg/kg

LCLo (inhalation/rat): > 4.6 mg/L, 75 min

2-Ethylhexan-1-ol:

LD<sub>50</sub> (inhalation/rat): >0.89 mg/L, 4 h

#### Skin corrosion/irritation

Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/irritation

May cause slight eye irritation.

#### Skin sensitisation

Not classified. The product does not contain substances classified as skin sensitisers above the classification thresholds.

#### Respiratory sensitisation

Not classified. The product does not contain substances classified as respiratory sensitisers above the classification thresholds.

#### Germ cell mutagenicity

Not classified. The product does not contain substances classified as mutagenic above the classification thresholds.

#### Carcinogenicity

Suspected of causing cancer.

#### Reproductive toxicity

Not classified. The product does not contain substances

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

	classified for reproductive toxicity above the classification thresholds.
<b>Specific Target Organ Toxicity – single exposure</b>	Not classified. The product does not contain substances classified for specific target organ toxicity after a single exposure above the classification thresholds.
<b>Specific Target Organ Toxicity – repeated exposure</b>	Not classified. The product does not contain substances classified for specific target organ toxicity after repeated exposure above the classification thresholds.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways. Risk of aspiration into lungs resulting in chemical pneumonia.

## Information on likely routes of exposure

<b>Inhalation</b>	Harmful if inhaled.
<b>Skin contact</b>	Harmful in contact with skin. Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
<b>Eye contact</b>	May cause slight eye irritation.
<b>Ingestion</b>	Harmful if swallowed. May be fatal if swallowed and enters airways. Risk of aspiration into lungs resulting in chemical pneumonia. Ingestion may cause discomfort and nausea.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Skin contact causes irritation and redness. Repeated exposure may cause skin dryness or cracking. Eye contact may cause slight irritation, watering and redness. If swallowed, aspiration into lungs may result in chemical pneumonia. Ingestion may cause discomfort and nausea.
---	---

<b>Mixture versus substance information</b>	No data available.
---	--------------------

<b>Other information</b>	None.
--------------------------	-------

## SECTION 12: Ecological Information

<b>12.1 Toxicity</b>	Toxic to aquatic life with long lasting effects.
	No data available on the mixture. The following data are for the product components:
	2-Ethylhexyl nitrate:
	LC <sub>50</sub> ( <i>Danio rerio</i> ): 2 mg/L, 96 h
	EC <sub>50</sub> ( <i>Daphnia magna</i> ): > 12.6 mg/L, 48 h
	EC <sub>50</sub> ( <i>Pseudokirchnerella subcapitata</i> ): 3.22 mg/L, 72 h

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

(growth rate)  
EC<sub>50</sub> (*Pseudokirchnerella subcapitata*): 1.57 mg/L, 72 h  
(yield)

Fuels, diesel, no. 2:  
LL<sub>50</sub> (*Oncorhynchus mykiss*): 21 mg/L, 96 h (WAF)  
(estimated using PETROTOX computer model)  
EC<sub>50</sub> (*Daphnia magna*): 210 mg/L, 48 h (WAF)  
EL<sub>50</sub> (*Daphnia magna*): 68 mg/L, 48 h (WAF)  
EL<sub>50</sub> (*Pseudokirchnerella subcapitata*): 22 mg/L, 72 h  
(growth rate)(WAF)  
NOEL (*Pseudokirchnerella subcapitata*): 1 mg/L, 72 h  
(growth rate)(WAF)  
NOEL (*Pseudokirchnerella subcapitata*): 1 mg/L, 72 h  
(biomass)(WAF)  
NOEC (*Oncorhynchus mykiss*): 0.083 mg/L, 14 days  
NOEC (*Daphnia magna*): 0.2 mg/L, 21 days (estimated  
using PETROTOX computer model)

## 12.2 Persistence and degradability

No data available on the mixture. The following data are for the product components:

2-Ethylhexyl nitrate:  
Not readily biodegradable.

Fuels, diesel, no. 2:  
Not readily biodegradable.

## 12.3 Bioaccumulative potential

2-Ethylhexyl nitrate:  
High potential to bioaccumulate.  
Log Pow: 3.74 – 5.24  
BCF: 1332

## 12.4 Mobility in soil

2-Ethylhexyl nitrate:  
Log Koc (soil/water partition coefficient): 3.75  
Volatile.

## 12.5 Results of PBT and vPvB assessment

The product does not contain substances assessed to be PBT or vPvB.

## 12.6 Other adverse effects

None known.

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

## SECTION 13: Disposal Considerations

### 13.1 Waste treatment methods

To be disposed of as hazardous waste. Disposal should be in accordance with local, state or national legislation.

Contaminated adsorbent must be removed in sealed, plastic lined drums and disposed of via an authorised waste disposal contractor. Do not empty into drains; dispose of this material and its container in a safe way.

## SECTION 14: Transport Information

### ADR

14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.

### ADN

14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.

### RID

14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

## IATA/ICAO

14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.

## IMDG

14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Marine pollutant.
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	The product is not intended to be transported in bulk.

## SECTION 15: Regulatory Information

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP), Directive 67/548/EEC & Directive 1999/45/EC.
15.2	Chemical Safety Assessment	Not applicable.

## SECTION 16: Other Information

Full text of relevant R-phrases and/or H-statements:

Hazard Statement(s):	H302: Harmful if swallowed. H304: May be fatal if swallowed and enters airways. H312: Harmful in contact with skin. H315: Causes skin irritation. H319: Causes serious eye irritation. H332: Harmful if inhaled.
----------------------	---

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

## Supplemental Hazard information (EU):

H335: May cause respiratory irritation.  
H351: Suspected of causing cancer.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H411: Toxic to aquatic life with long lasting effects.

## Risk phrase(s):

EUH044: Risk of explosion if heated under confinement.  
EUH066: Repeated exposure may cause skin dryness or cracking.  
R20: Harmful by inhalation.  
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.  
R36/37/38: Irritating to eyes, respiratory system and skin.  
R38: Irritating to skin.  
R40: Limited evidence of a carcinogenic effect.  
R44: Risk of explosion if heated under confinement.  
R65: Harmful: may cause lung damage if swallowed.  
R66: Repeated exposure may cause skin dryness or cracking.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## Abbreviations:

BCF:	Bioconcentration factor
bw:	Body weight
CAS:	Chemical Abstracts Service;
dw:	Dry weight
EINECS:	European Inventory of Existing Commercial Chemical Substances
EC <sub>50</sub> :	Effective Concentration 50%
EL <sub>50</sub> :	Effective Loading rate 50%
LC <sub>50</sub> :	Lethal Concentration 50%
LD <sub>50</sub> :	Lethal Dose 50%
LL <sub>50</sub> :	Lethal Loading rate 50%
LOEL:	Lowest Observed Effect Level
NOEL:	No Observed Effect Level
PBT:	Persistent, Bioaccumulative and Toxic.
vPvB:	Very Persistent and Very Bioaccumulative.
WAF:	Water Accommodated Fraction.

## References:

Supplier's Safety Data Sheets for ingredients  
ECHA REACH dossiers  
Approved Classification and Labelling Guide (Sixth edition)

# Safety Data Sheet



According to Regulation (EC) No. 1907/2006 (REACH)

---

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009  
Regulation (EC) No. 1272/2008 of the European Parliament and of the council.

## Disclaimer:

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE, BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM, IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

## Version history:

<b>Version:</b>	1.0
<b>Issue date:</b>	28/02/2014
<b>Previous Version:</b>	-
<b>Issue date of previous version:</b>	-
<b>Sections changed from previous version:</b>	-